DUCHESNE COUNTY MONUMENT SURVEY RECORD

LINE	BEARING	DISTANCE
L 1	S 38°14'43" E	20.22'
L2	S 33°02'20" W	19.87
L3	S 52°35'03" W	26.58'
L4	S 54°22'27" W	32.14'

T3S R4W

SEC 7 | SEC 8 SEC 18 | SEC 17

> U.S.B.&M. R-5

> > 7




S 89°17'51" W 2670.48

ĆOR

N 89°52'12" E 2659.70' WATER METER 5/8" REBAR WITH PLASTIC CAP Ω TELE PEDISTAL NAIL AND WASHER IN LEFT SIDE OF POWER POLE

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH
DERIVED FROM G.P.S. OBSERVATIONS AT A
CONTROL POINT (TOWNSHIP CORNER)
LOCATED AT LAT. 40°15'22.90258"N AND
LONG. 110°23'21.19760"W USING THE UTAH
STATE G.P.S. VIRTUAL REFERENCE STATION
CONTROL NETWORK MAINTAINED AND
OPERATED BY THE AUTOMATED GEOGRAPHIC
REFERENCE CENTER NOTE:



DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND DUCHESNE COUNTY 2½" DIA. ALUMINUM CAP ON 5/8" REBAR SET IN CONCRETE COLUMN AT QUARTER

DESCRIPTION OF MONUMENT AND ACCESSORIES
ESTABLISHED TO
PERPETUATE THE ORIGINAL
LOCATION OF THE CORNER

REFERENCED CORNER TO ADJACENT QUARTER CORNERS AS WELL AS REFERENCE POINTS SHOWN



MARKINGS ON MONUMENT

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7253585.535 F: 1955872.027 NAVD88 EL: 5924.22 FEET

LATITUDE: 40°13'39.00068"N **LONGITUDE:** 110°22'12.55170"W ELLIPSOID HEIGHT: 5868.46 FEET

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300030S0040W0_200500



PHOTO OF MONUMENT FACING EAST

CERTIFICATION

<u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>| | | DEC | | 7</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

